

Installation Manual for Metal Roof on a Gable Roof Pavilion



1. The first step will be to install the drip edge. You have to cut these to length. Fasten with one 1" screw. If you have staples or nails, that would be the proper way to fasten. Fasten one every 16".



2. Once you have all drip edges fastened, put the rubber enclosure on. Keep it up about 1½" to 2" from bottom of drip edge. This will just paste on. Do not stretch it too hard. The ribs have to line up with the rib of tin.



3. Installing the tin starting at one end. There will be an overlap and underlap on the tin. The underlap will have a small flange on. Always start with the overlap on the end of pavilion. Keep the bottom of tin flush with drip edge. Fasten with the 1" screws. You do not have to fasten way on the outside because the gable rake will hold that down. The first piece will have three screws at every lath. Make sure the first piece gets put on square or there will be a problem.



4. Continue with second piece. It just sits right on top of last rib. When you come to the last piece, you have to cut it to size.



5. Once you have all tin installed, fasten the gable trim. These you have to the angles on the top. Fasten with one 1" screw into fascia and one 1" screw into every lath on other side.



6. Continue with other side. Just butt them together and fasten.



7. When you have all four pieces of rake installed, put the ridge cap on this. You will want to put closure foam on before installing. Peel the plastic off the back then it will just stick to cap.



8. Fasten cap with one 1½" screw every 24" on both sides.

You have now completed your project.